

WHT9SYB

gorenje
Life Simplified

Freestanding wall decorative cooker hood



B

AdaptLight

Easy-to-clean filters

OptiStart



Recirculation mode



Touch control

Wall mounted cooker hood

Venting with air extraction or recirculation

Energy class: **B**

Material of housing/chimney: **Painted steel/glass / varnished steel**

Lightning efficiency class: **A**

Grease filtering efficiency class: **B**

Fluid dynamic efficiency class: **B**

Maximum extraction rate by extraction operation: **650 m³/h**

Maximum extraction rate by recirculation operation: **488 m³/h**

Venting tube diameter: **15 cm**

Air flow by extraction version, step 1: **235 m³/h**

Air flow by extraction version, step 2: **355 m³/h**

Air flow by extraction version, step 3: **650 m³/h**

Electronic control

Control setting: **Touch control**

Number of speed positions: **3**

OptiStart - just one push of the on/off button to start the hood

TouchFree Inox

Lamp type: **LED**

AdaptLight

Number of lights: **2**

Power of lights: **6 W**

Filter material: **Washable aluminium with polyurethane foam**

Coal filter code (optional as separate purchase): **698059**

Recirculation set number: **683038**

Number of motors: **1**

No return airflow flap: **150 mm**

Max. noise level: **70 dB(A)re 1 pW**

Height: **60 mm**

Min. height of the chimney: **740 mm**

Max. height of the chimney: **980 mm**

Annual energy consumption: **68.3 kWh**

Dimensions (W×H×D): **89.8 × 6 × 45.6 cm**

Dimensions of packed product (W×H×D): **100.6 × 54.1 × 49.3 cm**

Net weight: **16.7 kg**

Gross weight: **22.3 kg**

Connected load: **266 W**

Nominal current of fuse: **16 amp**

Product code: **732389**

EAN code: **3838782165412**



<https://international.gorenje.com/product/732389>